

# BRAUSSE | TA SERIES

Folding & Gluing Machine



## Outstanding Features



Individually adjustable feed belts with vibrator to ensure stable and smooth feeding (suction feed optional)



Standard 2 upper and 2 lower glue pots for versatile combination of gluing options



Touch Screen main control panel, user - friendly



Heavy duty trombone section to ensure stable transfer of products to compressing conveyor



Servomotor controlled back folding system for 4/6-corner boxes (optional)



Pocket Folder Device (optional)



## TA SERIES

FOLDING & GLUING MACHINE FOR FOLDING CARTON





### Standard Model:

TA650-C3 / TA650-C6

TA900-C3 / TA900-C6

TA1100-C3 / TA1100-C6

## Technical Specification

	<b>Straightline Cartons</b> A mm(in) B mm(in)	<b>TA 650</b> 100-700 (3.9-27.5) 78-700 (3-27.5)** 55-800 (2.2-31.5)	<b>TA 900</b> 120-900 (4.7-35.4) 80-900 (3.1-35.4)** 55-900 (2.2-35.4)	<b>TA 1100</b> 120-1100 (4.7-43.3) 80-1100 (3.1-43.3)** 55-1100 (2.2-43.3)
** with small box fold device				
	<b>Lockbottom Cartons</b> A mm(in) B mm(in) C min. mm(in) D min. mm(in) E min. mm(in) F min. mm(in)	<b>TA 650</b> 150-675 (5.9-26.6) 120-800 (4.7-31.5) 40 (1.57) 30 (1.2) 65 (2.56) 28 (1.1)	<b>TA 900</b> 160-875 (6.3-34.4) 150-900 (5.9-35.4) 47 (1.85) 30 (1.2) 65 (2.56) 28 (1.1)	<b>TA 1100</b> 160-1075 (6.3-42.3) 150-900 (5.9-35.4) 47 (1.85) 30 (1.2) 65 (2.56) 28 (1.1)
	<b>4-Corner Collapsible Boxes</b> A mm(in) B mm(in) C mm(in)	<b>TA 650</b> 160-600 (6.3-23.6) 160-700 (6.3-27.5) 30-100 (1.2-3.9)	<b>TA 900</b> 175-850 (6.9-33.5) 160-700 (6.3-27.5) 30-150 (1.2-5.9)	<b>TA 1100</b> 175-1050 (6.9-41.3) 160-700 (6.3-27.5) 30-150 (1.2-5.9)
	<b>6-Corner Collapsible Boxes</b> A mm(in) B mm(in) C mm(in)	<b>TA 650</b> 280-600 (11.0-23.6) 160-700 (6.3-27.5) 30-100(1.2-3.9)	<b>TA 900</b> 300-850(11.8-33.5) 160-700(6.3-27.5) 30-150(1.2-5.9)	<b>TA 1100</b> 300-1050 (11.8-41.3) 160-700 (6.3-27.5) 30-150 (1.2-5.9)

Stock Range	Solid board, up to 800g/m <sup>2</sup> . Corrugated up to E-Flute
Fundamental Pattern	Straight Line, Double Wall, Crash-Lock Bottom, 4/6-Corner
Max. Belt Speed	425m/min.
Main Motor	15/22KW
Overall Length	12140/12740
Total Weight	7000-8500KG

In the interest of product improvement, the manufacturer reserves the right to change specifications and features without notice

## BRAUSSE GROUP

### Headquarter

#1 - 1500 Valmont Way  
Richmond, British Columbia  
Canada, V6V 1Y4  
1-888-853-4760

Tel: (604)278-2027

Fax: (604)278-1005

Email: [printech@can.rogers.com](mailto:printech@can.rogers.com)

### Brausse Group USA

1-888-272-8773

[WWW.BRAUSSE.COM](http://WWW.BRAUSSE.COM)

# BRAUSSE



*Brausse Group's State of the Art Manufacturing Facility in Shanghai, China.*

## The Brausse Group

Brausse Group is the world's leading equipment manufacturer for the converting industry, with manufacturing bases worldwide. We have been supplying converting equipment to many different industries for over 25 years. The globalization of our manufacturing process enables us to maintain the highest level of product quality and innovation, at the best economical value.

Many of our facilities are either ISO9001:2000, CE and/or CSA certified for their first class workmanship. We have teams of highly trained service professionals ready to serve you because we believe that service is "the name of the game" in your daily operation.